

Safety Data Sheet

Diesel

Replaces date: 10/05/2016
Íslensk aðlögun 31/5/2021

Revision date: 17/08/2018
Version: 2.1.0

SECTION 1: Identification of the substance/preparation and of the company/undertaking

1.1. Product identifier

Trade name: Diesel
Synonyms: Automative gasoil

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended uses: Fuel.
Inadvisable uses: None.

1.3. Details of the supplier of the safety data sheet

Supplier

Company: Equinor ASA (Site: Mongstad)
Address: Forusbeen 50
Zip code: 4035
City: Stavanger
Country: NORWAY
E-mail: chem@equinor.com
Phone: +47 56 34 40 00

Atlantsolía
Lónsbraut 2
220
Hafnarfjörður
Ísland
atlantsolia@atlandsolia
591-3100

1.4. Emergency Telephone Number

1 1 2

Eitrunarmiðstöð Landspítalans 543 2222

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

CLP-classification: Flam. Liq. 3;H226 Asp. Tox. 1;H304 Skin Irrit. 2;H315 Acute Tox. 4;H332 Carc. 2;H351 STOT RE 2;H373 Aquatic Chronic 2;H411

Most serious harmful effects: Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Harmful if inhaled. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Pictograms



Signal word: Danger

Contains

Substance: Fuels, Diesel;

Safety Data Sheet

Diesel

Replaces date: 10/05/2016

Revision date: 17/08/2018

Version: 2.1.0

H-phrases

| | |
|------|--|
| H226 | Flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H332 | Harmful if inhaled. |
| H351 | Suspected of causing cancer. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H411 | Toxic to aquatic life with long lasting effects. |

P-phrases

| | |
|----------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P301/310 | IF SWALLOWED: Immediately call a POISON CENTER/doctor. |
| P331 | Do NOT induce vomiting. |

2.3. Other hazards

The product does not contain any PBT or vPvB substances.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| Substance | CAS No | EC No | REACH Reg. No. | Concentration | Notes | CLP-classification |
|---|------------|-----------|-----------------------|---------------|-------|--|
| Fuels, Diesel | 68334-30-5 | 269-822-7 | 01-2119484664-27-0019 | 93 - 100% | | Flam. Liq. 3;H226 Asp. Tox. 1;H304 Skin Irrit. 2;H315 Acute Tox. 4;H332 Carc. 2;H351 STOT RE 2;H373 Aquatic Chronic 2;H411 |
| Fatty acids, C16-18 and C18-unsaturated., Methyl esters | 67762-38-3 | 267-015-4 | 01-2119471664-32 | 0 - 7% | | |
| 2-ethylhexyl nitrate | 27247-96-7 | 248-363-6 | 01-2119539586-27-0022 | 0.05 % | | Acute Tox. 4;H312 Acute Tox. 4;H332 |

Please see section 16 for the full text of H-phrases.

Ingredient comments: Max. 10 mg/kg sulphur.

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|----------------------|--|
| Inhalation: | Seek fresh air. Seek medical advice in case of persistent discomfort. |
| Ingestion: | Wash out mouth thoroughly and drink 1-2 glasses of water in small sips. Do not induce vomiting. If vomiting occurs, keep head low so that stomach contents do not enter lungs. Immediately call a POISON CENTER or doctor/physician. |
| Skin contact: | Remove contaminated clothing. Wash skin with soap and water. Seek medical advice in case of persistent discomfort. |
| Eye contact: | Flush with water (preferably using eye wash equipment) until irritation subsides. Seek medical advice if symptoms persist. |

Safety Data Sheet

Diesel

Replaces date: 10/05/2016

Revision date: 17/08/2018
Version: 2.1.0

Burns: Flush with water until pain ceases. Remove clothing that is not stuck to the skin - seek medical advice/transport to hospital. If possible, continue flushing until medical attention is obtained.

General: When obtaining medical advice, show the safety data sheet or label.

4.2. Most important symptoms and effects, both acute and delayed

Harmful by inhalation. Irritating to skin - may cause reddening. May cause chemical pneumonia if ingested or vomited. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. The product releases organic solvent vapours which may cause lethargy and dizziness. At high concentrations, the vapours may cause headache and intoxication.

4.3. Indication of any immediate medical attention and special treatment needed

No special immediate treatment required. Treat symptoms.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media: Extinguish with powder, foam or water mist. Use water or water mist to cool non-ignited stock.

Unsuitable extinguishing media: Do not use water stream, as it may spread the fire.

5.2. Special hazards arising from the substance or mixture

Can generate harmful flue gases containing carbon monoxide in the event of fire.

5.3. Advice for fire-fighters

Move containers from danger area if it can be done without risk. Avoid inhalation of vapour and flue gases - seek fresh air. Wear Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Wear respiratory protective equipment. Wear gloves. Wear suitable protective clothing. Wear safety goggles if there is a risk of eye splash. Stay upwind/keep distance from source. Keep unnecessary personnel away. Provide adequate ventilation. Smoking and naked flames prohibited.

For emergency responders: In addition to the above: Protective suit equivalent to EN 368, type 3, is recommended.

6.2. Environmental precautions

Prevent spillage from entering drains and/or surface water. Notify proper authorities in case of contamination of soil or aquatic environment or discharge to drains.

6.3. Methods and material for containment and cleaning up

Contain and absorb spill with sand or other absorbent, non-combustible material and transfer to suitable waste containers.

6.4. Reference to other sections

See section 8 for type of protective equipment. See section 13 for instructions on disposal.

Safety Data Sheet

Diesel

Replaces date: 10/05/2016

Revision date: 17/08/2018

Version: 2.1.0

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Work under effective process ventilation (e.g. local exhaust ventilation). A safety shower should be available. A workplace assessment must be conducted to ensure that employees are not exposed to effects that may involve a risk during pregnancy. Do not store, use and/or consume foods, beverages or tobacco products in the work room. Store personal protective equipment separately from other clothing. Wash hands before breaks, before using restroom facilities, and at the end of work.

7.2. Conditions for safe storage, including any incompatibilities

Store safely, out of reach of children and away from food, animal feeding stuffs, medicines, etc. Do not store with the following: Strong oxidisers. Store locked up. Keep in tightly closed original packaging. Store in a well-ventilated area.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit: Contains no substances subject to reporting requirements

Measuring methods: Compliance with the stated occupational exposure limits may be checked by occupational hygiene measurements.

Legal basis: [Rg. 390/2009, um mengunarmörk. Síðast breytt í nóvember 2020](#)

PNEC

| Fuels, Diesel, cas-no 68334-30-5 | | | | |
|----------------------------------|------------|-------------------|-------------------------|------|
| Exposure | Value | Assessment Factor | Extrapolation Method | Note |
| PNEC aqua (freshwater) | 0,083 mg/l | 1 | Statistic extrapolation | |

DNEL - workers

| Fuels, Diesel, cas-no 68334-30-5 | | | | | |
|--|-----------------------------|-------------------|-----------------|-----------------------|------|
| Exposure | Value | Assessment Factor | Dose Descriptor | Main Impact Parameter | Note |
| Dermal DNEL (long-term exposure - systemic effects) | 2,9 mg/m ³ /8h | 24 | NOEL | | |
| Inhalation DNEL (long-term exposure - systemic effects) | 68 mg/m ³ /8h | 7,5 | NOEL | | |
| Inhalation DNEL (acute/short-term exposure - systemic effects) | 4300 mg/m ³ /15m | 7,5 | NOAEC | | |

DNEL - general population

| Fuels, Diesel, cas-no 68334-30-5 | | | | | |
|----------------------------------|-------|-------------------|-----------------|-----------------------|------|
| Exposure | Value | Assessment Factor | Dose Descriptor | Main Impact Parameter | Note |

Safety Data Sheet

Diesel

Replaces date: 10/05/2016

Revision date: 17/08/2018

Version: 2.1.0

| | | | | | |
|--|-----------------------------|-----|-------|--|--|
| Inhalation DNEL (acute/short-term exposure - systemic effects) | 2600 mg/m ³ /15m | 7,5 | NOAEC | | |
| Dermal DNEL (long-term exposure - systemic effects) | 1,3 mg/kg | 24 | NOAEL | | |
| Inhalation DNEL (long-term exposure - systemic effects) | 20 mg/m ³ /24h | 7,5 | NOEL | | |

8.2. Exposure controls

| | |
|---|--|
| Exposure controls: | See enclosed exposure scenarios for further information. |
| Appropriate engineering controls: | Wear the personal protective equipment specified below. |
| Personal protective equipment, eyeface protection: | Wear safety goggles if there is a risk of eye splash. Eye protection must conform to EN 166. |
| Personal protective equipment, skin protection: | Wear suitable protective clothing. |
| Personal protective equipment, hand protection: | <p>Light use (small volume, shortterm contact (below 10 min.)): Wear gloves. Type of material: Nitrile rubber. Change gloves immediately if contaminated, and wash hands with soap and water.</p> <p>Medium use (medium volume, medium contact (1-2 hours)): Type of material: Nitrile rubber. Wear coveralls.</p> <p>Heavy use (high volume, longterm contact (more than 2 hours)): Wear gloves. Type of material: Nitrile rubber. Wear coveralls.</p> <p>Penetration time: >8 hours. Gloves must conform to EN 374.</p> |
| Personal protective equipment, respiratory protection: | <p>Light use (small volume, shortterm contact (below 10 min.)): Not required.</p> <p>Medium use (medium volume, medium contact (1-2 hours)): In case of insufficient ventilation, wear respiratory protective equipment. Filter type: A.</p> <p>Heavy use (high volume, longterm contact (more than 2 hours)): In case of insufficient ventilation, wear respiratory protective equipment. Filter type: A.</p> <p>Respiratory protection must conform to one of the following standards: EN 136/140/145.</p> |
| Environmental exposure controls: | Ensure compliance with local regulations for emissions. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Parameter | Value/unit |
|------------|------------------------------------|
| State | Liquid |
| Colour | Brown |
| Odour | Diesel. |
| Solubility | Insoluble in the following: Water. |

Safety Data Sheet

Diesel

Replaces date: 10/05/2016

Revision date: 17/08/2018

Version: 2.1.0

| | |
|----------------------|-----|
| Explosive properties | N/A |
| Oxidising properties | N/A |

| Parameter | Value/unit | Remarks |
|---|---------------------------|-----------|
| pH (solution for use) | No data | |
| pH (concentrate) | No data | |
| Melting point | -40 - 6 °C | |
| Freezing point | No data | |
| Initial boiling point and boiling range | 141 - 500 °C | |
| Flash Point | 65 °C | |
| Evaporation rate | No data | |
| Flammability (solid, gas) | | Flammable |
| Flammability limits | > 225 °C | |
| Explosion limits | No data | |
| Vapour pressure | 0.40 kPa | (40 °C) |
| Vapour density | No data | |
| Relative density | 0.80 - 0.91 | |
| Partition coefficient n-octanol/water | No data | |
| Auto-ignition temperature | > 225 °C | |
| Decomposition temperature | No data | |
| Viscosity | > 1.30 mm ² /s | (40 °C) |
| Odour threshold | No data | |

9.2 Other information

| Parameter | Value/unit | Remarks |
|-------------|------------|---------|
| Pour point: | -40 - 6 °C | |

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with the following: Strong oxidisers.

10.2. Chemical stability

The product is stable when used in accordance with the supplier's directions.

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid heating and contact with ignition sources.

10.5. Incompatible materials

Strong oxidisers.

10.6. Hazardous decomposition products

Product decomposes in fire conditions or when heated to high temperatures, and inflammable and toxic gases may be released.

Safety Data Sheet

Diesel

Replaces date: 10/05/2016

Revision date: 17/08/2018

Version: 2.1.0

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Fuels, Diesel, cas-no 68334-30-5

| Organism | Test Type | Exposure time | Value | Conclusion | Test method | Source |
|----------|-----------|---------------|-------------|------------|-------------|--------|
| Rat | LD50 | | > 7600mg/kg | | OECD 420 | |

The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met. Ingestion may cause discomfort.

Acute toxicity - dermal

Fuels, Diesel, cas-no 68334-30-5

| Organism | Test Type | Exposure time | Value | Conclusion | Test method | Source |
|----------|-----------|---------------|-------------------|------------|-------------|--------|
| Rabbit | LD50 | | 4300 mg/kg bw/day | | | |

The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met.

Acute toxicity - inhalation

Fuels, Diesel, cas-no 68334-30-5

| Organism | Test Type | Exposure time | Value | Conclusion | Test method | Source |
|----------|--------------|---------------|----------|------------|-------------|--------|
| Rat | LC50 (gases) | 4h | 4.1 mg/l | | OECD 403 | |

Harmful by inhalation.

Skin corrosion/irritation

Fuels, Diesel, cas-no 68334-30-5

| Organism | Test Type | Exposure time | Value | Conclusion | Test method | Source |
|----------|-----------|---------------|-------|------------|-------------|--------|
| Rabbit | | 24h | | Irritating | OECD 404 | |

Irritating to skin - may cause reddening.

Serious eye damage/eye irritation

Fuels, Diesel, cas-no 68334-30-5

| Organism | Test Type | Exposure time | Value | Conclusion | Test method | Source |
|----------|-----------|---------------|-------|----------------|-------------|--------|
| Rabbit | | 72h | | Non-irritating | OECD 405 | |

The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met. Temporary irritation.

Respiratory sensitisation or skin sensitisation

Fuels, Diesel, cas-no 68334-30-5

| Organism | Test Type | Exposure time | Value | Conclusion | Test method | Source |
|------------|-----------|---------------|-------|-----------------|-------------|--------|
| Guinea pig | | | | Non-sensitising | OECD 406 | |

The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met.

Germ cell mutagenicity

Fuels, Diesel, cas-no 68334-30-5

| Organism | Test Type | Exposure time | Value | Conclusion | Test method | Source |
|----------|-----------|---------------|------------|--------------------------------|-------------|--------|
| Rat | | | 3000 mg/kg | No mutagenic effects observed. | | |

Safety Data Sheet

Diesel

Replaces date: 10/05/2016

Revision date: 17/08/2018

Version: 2.1.0

The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met.

Carcinogenic properties

Fuels, Diesel, cas-no 68334-30-5

| Organism | Test Type | Exposure time | Value | Conclusion | Test method | Source |
|----------|-----------|---------------|-------|------------------------------|-------------|--------|
| Mouse | | 3 weeks | | Neoplastic effects observed. | OECD 451 | |

May cause cancer.

Reproductive toxicity

Fuels, Diesel, cas-no 68334-30-5

| Organism | Test Type | Exposure time | Value | Conclusion | Test method | Source |
|----------|------------------|---------------|------------------|------------|-------------|--------|
| | NOAEC Inhalation | | > 401ppm | | | |
| | NOAEL (Dermal) | | 125 mg/kg/day | | | |
| Rat | | 20d | 125 mg/kg bw/day | Negative | | |

The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met.

Single STOT exposure:

The product releases organic solvent vapours which may cause lethargy and dizziness. At high concentrations, the vapours may cause headache and intoxication. The product does not have to be classified. Test data are not available.

Repeated STOT exposure

Fuels, Diesel, cas-no 68334-30-5

| Organism | Test Type | Exposure time | Value | Conclusion | Test method | Source |
|----------|------------------|---------------|------------------|------------|-------------|--------|
| Rat | | | 500 mg/kg bw/day | | | |
| | Inhalation NOAEC | 90d | > 1710mg/m3 | | | |
| Rat | NOAEL (Dermal) | 28d | 0.5 ml/kg | | | |

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard:

May cause chemical pneumonia if ingested or vomited.

Other toxicological effects:

None known.

SECTION 12: Ecological information

12.1. Toxicity

Fuels, Diesel, cas-no 68334-30-5

| Organism | Species | Exposure time | Test Type | Value | Conclusion | Test method | Source |
|-----------|---------------------|---------------|-----------|------------|------------|-------------|--------|
| Fish | Oncorhynchus mykiss | 96h | 96hLL50 | 21 mg/l | | | |
| Crustacea | Daphnia magna | 48h | 48hEL50 | 68 mg/l | | | |
| Algae | | 72h | 72hIL50 | 22 mg/l | | | |
| Fish | Oncorhynchus mykiss | 14d | 14dNOEL | 0.083 mg/l | | | |

Safety Data Sheet

Diesel

Replaces date: 10/05/2016

Revision date: 17/08/2018

Version: 2.1.0

| | | | | | | | |
|-----------|---------------|-----|---------|-----------|--|--|--|
| Crustacea | Daphnia magna | 21d | 21dNOEL | 0.21 mg/l | | | |
|-----------|---------------|-----|---------|-----------|--|--|--|

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Fuels, Diesel, cas-no 68334-30-5

| Organism | Species | Exposure time | Test Type | Value | Conclusion | Test method | Source |
|----------|---------|---------------|-----------|-------|------------------------|-------------|--------|
| | | | | | Readily biodegradable. | | |

Not expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulation can be expected.

12.4. Mobility in soil

Not expected to be mobile in soil.

12.5. Results of PBT and vPvB assessment

The product does not contain any PBT or vPvB substances.

12.6. Other adverse effects

The product affects the pH value of the local aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Avoid release to the environment. Collect spills and waste in closed, leak-proof containers for disposal at the local hazardous waste site.

EWC code: Depends on line of business and use, for instance 13 07 01* fuel oil and diesel

Absorbent/cloth contaminated with the product: EWC code: 15 02 02 absorbents, filter materials (including oil filters not otherwise specified), wiping cloths, protective clothing contaminated by dangerous substances.

7023 Waste fuels and fuel oils

SECTION 14: Transport information

Land transport (ADR/RID)

| | | | |
|--|-------------|-------------------------------------|---|
| 14.1. UN-No.: | 1202 | 14.4. Packing group: | III |
| 14.2. UN proper shipping name: | DIESEL FUEL | 14.5. Environmental hazards: | The product must be labelled as an environmental hazard (symbol: fish and tree) in packaging sizes of more than 5 kg/l. |
| 14.3. Transport hazard class(es): | 3 | | |
| Hazard label(s): | 3 | | |
| Hazard identification number: | 30 | Tunnel restriction code: | D/E |

Safety Data Sheet

Diesel

Replaces date: 10/05/2016

Revision date: 17/08/2018

Version: 2.1.0

Other Information: -

Inland water ways transport (ADN)

| | |
|---|---|
| 14.1. UN-No.: 1202 14.2. UN proper shipping name: DIESEL FUEL 14.3. Transport hazard class(es): 3 Hazard label(s): 3 Transport in tank vessels: F + N2 | 14.4. Packing group: III 14.5. Environmental hazards: The product must be labelled as an environmental hazard (symbol: fish and tree) in packaging sizes of more than 5 kg/l. Other Information: - |
|---|---|

Sea transport (IMDG)

| | |
|--|---|
| 14.1. UN-No.: 1202 14.2. UN proper shipping name: DIESEL FUEL 14.3. Transport hazard class(es): 3 Hazard label(s): 3 EmS: F-E, S-E Other Information: - | 14.4. Packing group: III 14.5. Environmental hazards: The product must be labelled as a Marine Pollutant (MP) in packaging sizes of more than 5 kg/l. Environmental Hazardous Substance Name(s): Fuels, Diesel IMDG Code segregation group: - None - |
|--|---|

Air transport (ICAO-TI / IATA-DGR)

| | |
|---|---|
| 14.1. UN-No.: 1202 14.2. UN proper shipping name: DIESEL FUEL 14.3. Transport hazard class(es): 3 Hazard label(s): 3 | 14.4. Packing group: III 14.5. Environmental hazards: The product must be labelled as an environmental hazard (symbol: fish and tree) in packaging sizes of more than 5 kg/l. Other Information: - |
|---|---|

14.6. Special precautions for user

None.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Special Provisions: Special care should be applied for employees under the age of 18. Young people under the age of 18 may not carry out any work causing harmful exposure to this product.
 Directive 2012/18/EU (Seveso), E2 Hazardous to the Aquatic Environment in Category Chronic 2 : Column 2: 200 t, Column 3: 500 t.
 Directive 2012/18/EU (Seveso), P5c FLAMMABLE LIQUIDS: Column 2: 5000 t, Column 3:

Safety Data Sheet

Diesel

Replaces date: 10/05/2016

Revision date: 17/08/2018

Version: 2.1.0

50000 t.

Covered by:

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Regulation about the performance of work, use of work equipment and appurtenant

technical requirements, FOR-2011-12-06-1357. Latest amended by FOR-2013-06-18-658.

15.2. Chemical Safety Assessment

Other Information: Chemical safety assessments have been performed for the following substances:
 Fuels, diesel (68334-30-5 / 269-822-7)

SECTION 16: Other information

Version history and indication of changes

| Version | Revision date | Responsible | Changes |
|---------|---------------|-------------------------|---------|
| 2.1.0 | 17/08/2018 | Bureau Veritas HSE/ SRU | 1, 16 |
| 2.0.0 | 10/05/2016 | CGJ/Bureau Veritas HSE | 1-16 |

Abbreviations:

PBT: Persistent, Bioaccumulative and Toxic

vPvB: Very Persistent and Very Bioaccumulative

STOT: Specific Target Organ Toxicity

DNEL: Derived No Effect Level

PNEC: Predicted No Effect Concentration

References to literature and data sources:

Exposure scenario

Other Information:

This safety data sheet has been prepared for and applies to this product only. It is based on our current knowledge and the information that the supplier was able to provide about the product at the time of preparation. The safety data sheet complies with applicable law on preparation of safety data sheets in accordance with 1907/2006/EC (REACH) as subsequently changed.

Training advice:

A thorough knowledge of this safety data sheet should be a prerequisite condition.

Classification method:

Calculation based on the hazards of the known components. Test data.

List of relevant H-statements

| | |
|------|--|
| H226 | Flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H332 | Harmful if inhaled. |
| H351 | Suspected of causing cancer. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H411 | Toxic to aquatic life with long lasting effects. |

Quality assurance of SDS:

Bureau Veritas HSE Danmark /KDC

SDS is prepared by

Safety Data Sheet

Diesel

Replaces date: 10/05/2016

Revision date: 17/08/2018

Version: 2.1.0

Company: Bureau Veritas HSE Denmark A/S
Address: Oldenborggade 25
Zip code: 7000
City: Fredericia
Country: DENMARK
E-mail: infohse@dk.bureauveritas.com
Phone: +45 75 50 88 11
Fax: +45 75 50 88 10
Homepage: www.hse.bureauveritas.dk

Íslensk Aðlögun
Mannvit
Urðarhvarf 6
203
Kópavogur
Ísland mannvit@mannvit.is
422 3000
www.mannvit.is

Document language: GB